

Dräger X-am 3000

Dräger X-am 3000 is an innovative 2, 3- or 4 gas warning device. This small and lightweight instrument reliably monitors H₂S, CO, O₂ and combustible gases in ambient air. Its compact design combined with state of the art electronics ensures that it is ideally suited for gas detection requirements in all applications and industries.



ST-60048-2004

RUGGED AND DURABLE

Protection against dust and water is standard and ensures reliable operation in all environments. The optional rubber-boot gives additional protection for the Dräger X-am 3000 from bumps and hits.

EASY TO USE

A large display enables the easy identification of the measured values. The simple 3-button operation and an easy to use menu ensure intuitive operation. The visible menu makes selecting and performing other functions quick and simple.

INTELLIGENT SENSORS

DrägerSensors® are our own innovative technology that make safety work for you.

ROBUST AND WATER-TIGHT

The precalibrated electrochemical sensors, and the catalytic sensor are automatically recognized and provide precise and reliable measuring results. All Dräger sensors show a fast and accurate response to changing gas concentrations.

DISTINCTIVE ALARMS

In addition to a very loud audible alarm and a visual alarm, a vibrating alarm is integrated in the instrument. The functionality and the battery status are monitored continuously and will, if necessary generate an alarm. TWA and STEL are also evaluated. Different alarm cadences indicate pre and main alarm conditions.

OPTIONAL BUILT-IN PUMP

An optional internal pump which can be used together with up to 20 m / 66 ft. tubing is ideal for confined space applications. A convenient pump adapter makes it easy to switch between pump and diffusion mode.



ST-127-2004

Dräger X-am 3000:
Designed for the harshest industrial environments.

Fast. Accurate.

Innovative technology.



BATTERY AND CHARGING OPTIONS

The Dräger X-am 3000 comes standard with a NiMH battery pack. An alkaline pack is available for emergency backup and when power is not available for recharging. Charging options, including a car charging adapter, are available to meet your specific requirements.

DISTINCTIVE ALARMS

A life signal assures full functionality of the instrument without a visual check by the operator. The Dräger X-am 3000 stores all maximum values in its memory for later viewing. When using a calibration gas mixture, the instrument can be calibrated by pressing a single button.

DATALOGGER OPTION

Dräger X-am 3000 can be fitted with a datalogger, which records gas concentrations and alarms for >60 hours.

DRÄGER E-CAL COMPATIBLE

E-Cal provides automatic calibration and documentation of instrument service records.

APPROVALS

Dräger X-am 3000 has worldwide approvals: UL, ATEX, CSA and MSHA.

For more information:
www.draeger.com



TECHNICAL DATA

Multi gas measuring and warning device for 2, 3 or 4 gases: H₂S, CO, O₂ and combustible gases and vapors.


Size (h x w x d, approx.)	90 x 140 x 55 mm, 3.5" x 5.5" x 2.2"	
Weight (approx.)	550 g, 19.4 oz.	
Ambient conditions	Temperature	- 20 to + 55 °C; - 5 to + 130 °F continuous - 40 to + 55 °C; - 40 to + 130 °F short term -25 to + 50 °C; -13 to + 122 °F alkaline temp. range
	Pressure	700 to 1300 hPa, 20.7 to 38.4 inch Hg
	Humidity	10 to 95 %RH
Enclosure rating	IP 65	
Typical battery life	Alkaline	> 24 hours (diffusion mode) > 12 hours (pump mode)
	NiMH	> 18 hours (diffusion mode) > 12 hours (pump mode)
Audible alarm	> 90 dB (A) at a distance of 30 cm; 1ft.	
Charging time	< 4 hours	
Pump mode	Maximum length of tubing 20 m, 66 ft.	
Approvals	ATEX	II 2G EEx ia d IIC T4; - 25 ≤ Ta ≤ + 55 °C I M2 EEx ia d I
	UL	Class I, Div 1, Group A, B, C, D; Temp Code T4
	CSA	Class I, Div 1, Group A, B, C, D; Temp Code T4
	MSHA	Methane air mixtures
	CE-mark	electromagnetic compatibility (directive 89/336/EEC)

ORDER INFORMATION



Dräger X-am 3000:

Optional internal pump – ideal for confined space applications.



E-Cal Module

Automatic calibration and documentation.

Description	Order No.
X-am 3000; Ex, O ₂ , CO, H ₂ S Confined Space Kit	4543721
X-am 3000; Ex, O ₂ , H ₂ S Confined Space Kit	4543720
X-am 3000; Ex, O ₂ , CO Confined Space Kit	4543719
X-am 3000; Ex, O ₂ Confined Space Kit	4543740
X-am 3000; Ex, O ₂ , CO, H ₂ S with internal pump	4543718
X-am 3000; Ex, O ₂ , H ₂ S with internal pump	4543717
X-am 3000; Ex, O ₂ , CO with internal pump	4543716
X-am 3000; Ex, O ₂ with internal pump	4543739
X-am 3000; Ex, O ₂ , CO, H ₂ S	4543715
X-am 3000; Ex, O ₂ , H ₂ S	4543714
X-am 3000; Ex, O ₂ , CO	4543713
X-am 3000; Ex, O ₂	4543738
Datalogger Option (factory installed)	4543625
Power Supply, 12VDC, Automotive Plug	8317754
Battery Pack, NiMHY	8317709
Battery Pack, Alkaline (requires 4 'AA' alkaline batteries)	8317716
Protective Rubber Boot with shoulder strap	8317727
Deluxe Carry Case with shoulder strap	8317726
Nylon Carrying Case with shoulder strap	8317720
Float Probe	6802337
12" Clear Plastic Sample Probe	4511262
Bar Probe 3 ft. (90 cm)	8316532
Sampling Hose, Tygon (per foot)	4594707
Calibration Gas Flow Regulator	4557020
Calibration Gas Mixture - CH ₄ , O ₂ , CO, H ₂ S - 34L	4594639
PC communication cable	4530120
GasVision® Software for Data Download and Data Management	8314034
CC-Vision® Software for instrument configuration	6408515
X-am 3000 Operator Training CD – PPT	4543701
X-am 3000 E-Cal Module	8317719

www.draeger.com

USA

Draeger Safety, Inc.
101 Technology Drive
Pittsburgh, PA 15275-1057
USA
Tel +1 412 787-8383
Fax +1 412 787-2207

Customer Service
Tel +1 800 858-1737
Fax +1 800 922-5519

CANADA

Draeger Safety Canada Ltd.
7555 Danbro Crescent
Mississauga, ON L5N 6P9
Canada
Tel +1 905 821-8988
Fax +1 905 821-2565

sales.canada@draeger.com

MEXICO

Draeger Safety S.A. de C.V.
Av. Peñuelas No. 5
Bodega No. 37
Fraccionamiento Industrial
San Pedrito
Querétaro, Qro C.P. 76148
Mexico

Tel +1 52 442 246 1113
Fax +1 52 442 246 1114
ventas.mexico@draeger.com

GERMANY

Dräger Safety AG & Co. KGaA
Revalstrasse 1
23560 Lübeck
Germany

Customer Service
Tel +49 451 882-0
Fax +49 451 882-2080