



- DualSense® Technology increases worker safety by using two sensors to detect the same gas
- Guaranteed for Life™ with replaceable sensors and batteries that extends the life of the instrument
- Optional AlarmAmp™ increases audible alarms to 110dB
- Acknowledgeable gas alerts

INSTRUMENT CONFIGURATIONS

PART NUMBER	DESCRIPTION
TX1-1	Tango TX1, CO
TX1-2	Tango TX1, H ₂ S
TX1-4	Tango TX1, NO ₂
TX1-5	Tango TX1, SO ₂
TX1-G	Tango TX1, CO/H ₂ low

ACCESSORIES

18109330-ABC-ABC	DSX™ Docking Station for Tango™ TX1 A – DSX Mode: 0 = DSX Standalone, 1 = DSXi Cloud-connected, 2 = DSX-L Local Server B – Number of Gas Inlet Ports: 3 = 3 Ports, 6 = 6 Ports C – Power Cord Type: 1 = North America, 2 = Europe, 3 = Australia, 4 = UK
17154367	Replacement battery
18109171	Soft nylon case, Black
18109239	Soft nylon case, Safety Orange
18109218	Dust barrier kit, 5 pack
18109230	Water barrier kit, 5 pack
18109238	CalCup and tubing kit
17120908	Belt clip
17154915-0	AlarmAmp™, Black
17154915-1	AlarmAmp™, Safety Orange
17154916	Black nameplate
17154917	Green nameplate
17154918	Yellow nameplate
17154919	Blue nameplate
17154920	White nameplate

* These specifications are based on performance averages and may vary by instrument.

** Operating temperatures above 50 °C (122 °F) may cause reduced instrument accuracy. Operating temperatures below -20 °C (-4 °F) may cause reduced instrument accuracy and affect display and alarm performance.

Patent No. 9,000,910 – DualSense® Technology | Patent No. 9,064,386 – AlarmAmp™

SPECIFICATIONS*

INSTRUMENT WARRANTY:

Guaranteed for Life™. Warranted for as long as the instrument is supported by Industrial Scientific Corporation (excludes sensors, batteries, and filters). CO and H₂S sensors are warranted for three years. All other sensors are warranted for two years.

DISPLAY:

Segment liquid crystal display (LCD)

KEYPAD:

Two buttons

CASE MATERIALS:

Case top: Polycarbonate with a protective rubber overmold
Case bottom: Conductive polycarbonate

ALARMS:

Three strobe-emitting visual alarm LEDs (two red; one blue);
100 decibel (dB) audible alarm at a distance of 10 cm (3.94 in); Vibration alarm

DIMENSIONS:

99 x 51 x 35 mm (3.9 x 2.0 x 1.4 in)

WEIGHT:

126.0 g (4.4 oz)

TEMPERATURE RANGE:

-40 °C to 50 °C (-40 °F to 122 °F) **

HUMIDITY RANGE:

15%-95% Non-condensing (continuous)

SENSORS:

CO, CO/H₂, H₂S, NO₂, SO₂ – Electrochemical sensor technology

SENSOR MEASURING RANGES:

Carbon Monoxide (CO):	0 to 1,000 ppm in 1 ppm increments
Carbon Monoxide (CO/H ₂ low):	0 to 1,000 ppm in 1 ppm increments
Hydrogen Sulfide (H ₂ S):	0.0 to 500.0 ppm in 0.1 ppm increments
Nitrogen Dioxide (NO ₂):	0.0 to 150.0 ppm in 0.1 ppm increments
Sulfur Dioxide (SO ₂):	0.0 to 150.0 ppm in 0.1 ppm increments

BATTERY:

3.6 V Primary lithium-thionyl chloride (Li-SOCl₂); 1.5AH, 2/3AA; replaceable;
non rechargeable; always on; up to 2-year run time depending on operating conditions

DATA LOGGING:

3 months at 10-second intervals

EVENT LOGGING:

60 alarm events

CERTIFICATIONS

INGRESS PROTECTION:

IP66; IP67

-40 °C to 50 °C (-40 °F to 122 °F)

ATEX: Ex ia I Ma; Ex ia IIC T4 Ga;
Equipment Group and Category: I M1 and II 1G

CSA : Class I, Groups A B C D T4; Ex ia IIC T4

IECEX: Ex ia I Ma; Ex ia IIC T4 Ga

UL (C-US): Class I, Groups A B C D T4; Class II, Groups E F G;
Class I, Zone 0, AEx ia IIC T4

INMETRO: Ex ia I Ma; Ex ia IIC T4 Ga

-20 °C to 50 °C (-4 °F to 122 °F)

China Ex: Ex ia IIC T4 Ga

CMA: Ex ia I Ma; H2S, CO

KC: Ex ia IIC T4

EAC: PO Ex ia I X; 0 Ex iX IIC T4 X

**INDUSTRIAL
SCIENTIFIC**

www.indsci.com/tango

AMERICAS

Phone: +1-412-788-4353 | Fax: +1-412-788-8353

1-800-DETECTS (338-3287) North America

info@indsci.com

ASIA PACIFIC

Phone: +65-6561-7377

Fax: +65-6561-7787

info@ap.indsci.com

EMEA

Phone: +33 (0)1 57 32 92 61

Fax: +33 (0)1 57 32 92 67

info@eu.indsci.com